

Titan Laser 37000 WU

37,000 ISO / 33,000 ANSI Lumens | Contrast Ratio: 18,000:1 (Dynamic Black) / 2,000:1 Native | Part No:119-704

TITAN LASER SERIES DIGITAL PROJECTORS



THE VISIONARIES CHOICE

Colour System:

Laser Phosphor

DMD Specification:

Display capability upto WUXGA
2.3 megapixels pixels on screen at WUXGA

Display Type:

3 x 0.96" WUXGA DMD™

Fast transit pixels for smooth greyscale and improved contrast.

Display resolutions WUXGA (1920 x 1200)

Aspect Ratio:

16x10

Fill Factor

87%

Key Features

Video & Graphics Processing

- DisplayPort 1.2
- 2 x HDMI 2.0b HDCP 2.2
- HDR processing
- 2 x HDMI 1.4b HDCP 1.4 for Dual Pipe processing and Frame Sequential 3D Format.
- Sequential Processing: 3D via single HDMI 1.4b input
- Dual Pipe Processing: 3D Left and Right eyes via two HDMI 1.4b inputs.
- Synchronisation of active glasses.
- 3G-SDI with loop-through.
- DICOM simulation mode.
- DMX Art-Net

General Features

- Constant Brightness control
- Multi-Projector Brightness control
- Compatible with selected competitor lenses via lens converter
- Selectable EDID
- Custom Start-up Logo

Geometry Correction

- 4-Cornerstone, Vertical & Horizontal Keystone, Pincushion & Barrel, Arc and Image Rotation
- Non-linear warp

- Digital Zoom, Pan and Scan
- Blanking control for custom input window sizing.
- Scaling available for fixed aspect ratio screens.
- Unscaled processing for pixel mapped display

Edge Blending

- Blending control available for all sides with width control.
- Correction for non-active pixels at the edge of the display.
- Electronic Black Level Compensation.

Picture in Picture

- Two sources can be displayed simultaneously using 2D inputs. either picture in picture (PIP) , or side by side (PBP), with the original aspect ratios maintained.

HDBaseT® Interface

- Built in support for reception of uncompressed High Definition Video over standard CAT5e/6 LAN cable
- Allows projector to be placed up to 100m from source with low cost cabling
- Supports up to 4K UHD 3840 x 2160@60Hz 4:2:0 or 4K UHD 3840 x 2160@30Hz 4:2:2

Colour Processing

- Four colour modes available
- Powerful seven point colour correction for accurate colour matching with presets.
- Easy colour temperature selection
- Manual seven point colour adjustment
- Traditional lifts and gains

Projector Controller Software

- Intuitive user interface for network control
- Simultaneous control of user-defined groups of projectors
- At-a-glance monitoring of projector status

Projector Automation

- Real-time clock provides daily on/off automation
- E-mail alerts for system status

Source Compatibility:

2D Graphics standards up to 4K-UHD 3840x2160 resolution at 60Hz via HDMI 2.0, HDBaseT (4:2:0), DisplayPort inputs

3D Graphics standards up to dual-pipe WUXGA 120Hz via HDMI 1.4b inputs

3G-SDI is SMPTE 292M, SMPTE 259M-C and SMPTE 424M compliant.

Inputs/Outputs

Video & Computer			Communication & Control		
Type	Connector	Qty	Type	Connector	Qty
DisplayPort 1.2 (2D)	DisplayPort	1	3D Sync In	BNC	1
HDMI 1.4b (3D)	HDMI	2	3D Sync Out	BNC	1
HDMI 2.0b (2D)	HDMI	2	LAN	RJ45	2
3G-SDI in (2D)	BNC	1	RS-232	9-pin D-Sub	1
3G-SDI out	BNC	1	Wired Remote	3.5mm Stereo Jack	1
HDBaseT/LAN (2D)	RJ45	1	12V Trigger	3.5mm Stereo Jack	2
			3D Sync IR Out	BNC	1

3D Formats Supported	HDTV Formats Supported
Sequential / 1080p @ 100Hz	1080p (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)
Sequential / 1080p @ 120Hz	1080i (50Hz, 60Hz)
Sequential / WUXGA @ 100Hz (RB)	720p (50Hz, 60Hz)
Dual -Pipe / 1080p @ 50Hz	2K (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)
Dual -Pipe / 1080p @ 60Hz	4K-UHD (24Hz, 25Hz, 30Hz, 50Hz, 60Hz)
Dual -Pipe / WUXGA @ 50Hz (RB)	
Dual -Pipe / WUXGA @ 60Hz	

Computer Compatibility	Bandwidth
2D 4K-UHD upto 60Hz	498 Mpixels/sec via DisplayPort and HDMI2.0.
3D Supported Formats will be displayed upto WUXGA	

Remote Control	Automation Control
Addressable IR remote Control, Wireless and wired. On-Board keypad	Crestron RoomView Connected LAN RS-232 AMX (Device Discovery) DMX Art-Net Served web pages (Projector status, Projector control, Crestron RoomView, Network settings, Alert mail setup, Time setup, Error log, On screen Display)

Colour Temperature
3200K to 9300K

Lamp Type	Typical Lamp Life
Laser Light Source	20,000 hours

Lenses			
Lens	Part No.	Optimised Focus Range	Lens Shift
0.67:1 fixed HB	105-607	1.1m - 10m	Vert: 0.108 (U) 0.108 (D) frame, Hor: 0.044 (L) 0.044 (R) frame
1.12:1 fixed HB	105-608	3m - 15m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.16 - 1.49:1 zoom HB	109-236	3m - 15m	Vert: 0.408 (U) 0.408 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.39 - 1.87:1 zoom HB	105-610	4m - 24m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
1.87 - 2.56:1 zoom HB	105-611	4m - 24m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
2.56 - 4.16:1 zoom HB	105-612	9.1m - 45m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
4.16 - 6.96:1 zoom HB	105-613	12m - 80m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame
6.92 - 10.36:1 zoom HB	109-235	12m - 80m	Vert: 0.567 (U) 0.45 (D) frame, Hor: 0.188 (L) 0.188 (R) frame

Lens Mount
Motorised Shift, Zoom and Focus.(Lenses 0.67:1 & 1.12:1 have manual focus, shift is motorised) Intelligent Lens Memory with 10 user-definable pre-set positions for zoom lenses.

Mechanical Mounting	Orientation
Front/Rear Table Front/Rear Ceiling Adjustable Front/Rear Feet	Table Top or Inverted: Yes Pointing Up: Yes Pointing Down: Yes Roll (Portrait): Yes

Power Requirements	Power Consumption
200VAC to 230VAC, 50/60Hz single phase	Typical: 3100W , Maximum 3400 W

Thermal Dissipation	Fan Noise
Max 11430 BTU/Hour @ 200VAC BTU/Hour	Normal Mode: 50dBA, Max 52dBA Eco Typ: 47dBA

Operating/Storage Temperature	Operating Humidity
Operating: Full Power 0°C ~ 35°C (32°F ~95°F), ECO upto 40°C (104°F) Storage: -20°C ~ 60°C (-4°F ~ 140°F)	Operating: 10% ~ 90% non-condensing Storage: 10% ~ 90% non-condensing

Weight (Chassis Only)	Dimensions
95 kg 209 lb	L: 969.3mm, W: 650mm, H: 397.3mm (Excl handles) L: 38.2in, W: 25.6in, H: 15.6in (Excl handles)

Safety & EMC Regulations

UL, CB, CCC, KC, RoHS (CN), FCC Class A, FDA, CE,
IEC EN 60825-1 Class 3R Laser Product, IEC EN 62471-
5 Risk Group 3, WEEE (UK)

Accessories

Accessory	Part No.
Infrared Remote Control (Replacement)	118-678
Optional lens mount insert for selected competitor lenses	119-729

**Dimensions included for reference only and are subject to change. Please download the full set of CAD files for this display for more accurate information.*

Downloads

[PDF CAD Drawings](#)

[User Guides](#)

[AUTOCAD Drawings](#)

[User Guides German](#)

[User Guides French](#)

[Important Information](#)



Certificate Number 13629
ISO 9001

Specifications subject to change without notice. Digital Projection version: - ©2016 Digital Projection.
DLP®, Digital Light Processing™ and DMD are trademarks of Texas Instruments, Inc

DIGITAL PROJECTION, LTD GREENSIDE WAY, MIDDLETON MANCHESTER, UK. M24 1XX
T: +44.161.947.3300 | F: +44.161.684.7674 | www.digitalprojection.co.uk

DIGITAL PROJECTION, INC 55 CHASTAIN ROAD, SUITE 115 KENNESAW, GA. 30144
T: 770.420.1350 | F: 770.420.1360 | www.digitalprojection.com

DIGITAL PROJECTION, CHINA Rm A2006, ShaoYaoJu 101 North lane, Shi AO International Center, Chao Yang District, Beijing, 100029, PR CHINA
T: +86.10.58239771 | F: +86 10 58239770

DIGITAL PROJECTION, ASIA 16 NEW INDUSTRIAL ROAD, #02-10 HUDSON TECHNOCENTRE SINGAPORE 536204
T: +65.6284.1138 | F: +65.6284.1238